

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

Printing date 16.06.2015 Revision: 16.06.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: Casite Motor Honey Engine Oil Leak Stopper
- · Article number: C168, C168-12, C168G
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Oil additive.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Casite Intraco, LLC 530 Stephenson Highway Troy, MI 48083

Phone: 248-585-6909 Toll Free: 1-888-CASITE1

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



health hazard

Carc. 1B H350 May cause cancer.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling: Distillates (petroleum), hydrotreated heavy paraffinic

(Contd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 1)

· Hazard statements

H350 May cause cancer.

· Precautionary statements

The following Precautionary Statements are applicable only to the OSHA GHS regulations and not the specific CLP regulation: P280.

The following Precautionary Statements are applicable only to the EU CLP regulations and not the OSHA GHS regulations: P281.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection.

P281 Use personal protective equipment as required.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Restricted to professional users.

- · Hazard description:
- · WHMIS-symbols:

As of 11 February 2015, the current WHMIS system is being replaced by the GHS system. This is the classification under the older system.

D2A - Very toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0

1 Fire = 1

REACTIVITY | Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

HMIS Long Term Health Hazard Substances

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8	Distillates (petroleum), hydrotreated heavy paraffinic Carc. 1B, H350	50-100%
CAS: 25038-36-2	Ethylene/propylene/diene terpolymer © Eye Irrit. 2, H319	1-5%

· Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

- · Hazards May cause cancer.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Water haze or fog

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use personal protective equipment as required.

Particular danger of slipping on leaked/spilled product.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Remove from the water surface (e.g. skim or suck off).

Dispose contaminated material as waste according to section 13.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid the formation of oil haze.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

When heated the product forms flammable fumes.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

(Contd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 4)

- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

PEL (USA) Long-term value: 5 (mist) mg/m³ TLV (USA) Long-term value: 5 (mist) mg/m³

- DNELs No further relevant information available.
- · PNECs No further relevant information available.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

For large spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.


Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



(Contd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 5)

- · Body protection: Oil resistant protective clothing
- · Limitation and supervision of exposure into the environment Avoid release to the environment.
- · Risk management measures See Section 7 for additional information.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Gold coloured
Odour: Petroleum-like
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range:

Boiling point/Boiling range:

Flash point:

Not Determined.

> 225 °C (> 437 °F)

> 247 °C (> 477 °F)

Flammability (solid, gaseous): Not applicable.
 Auto/Self-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

· **Self-igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

Vapour pressure at 20 °C (68 °F): <.001 mmHg

Density at 20 °C (68 °F): 0,87 g/cm³ (7,26 lbs/gal)

Relative density Not determined.

Vapour density at 20 °C (68 °F) >1 g/cm³ (>8,345 lbs/gal)

• **Evaporation rate** Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 7)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with strong oxidising agents.

Reacts with strong acids.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

· 10.4 Conditions to avoid

Store away from oxidising agents.

Keep ignition sources away - Do not smoke.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Under fire conditions only:

Carbon monoxide and carbon dioxide

Hydrocarbons

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification: None.
- · Primary irritant effect:
- Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Subacute to chronic toxicity: May cause cancer.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

0 % of the mixture consists of component(s) of unknown toxicity.

- Acute effects (acute toxicity, irritation and corrosivity): None.
- · Repeated dose toxicity: Danger of very serious irreversible effects.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 1B

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity May cause cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 7)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · **Aquatic toxicity:** The material is harmful to the environment.
- 12.2 Persistence and degradability The product is biodegradable after prolonged adaptation.
- · 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

- · 12.4 Mobility in soil No further relevant information available.
- **Ecotoxical effects:**
- · Remark:

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Product is recyclable as a waste oil. Deliver unused and/or contaminated product to waste oil collectors. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to local official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

DOT, ADR, ADN, IMDG, IATA

Not Regulated

· 14.2 UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Not Regulated

(Contd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Not Regulated

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic Categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

(Contd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients are listed.

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H319 Causes serious eye irritation.

H350 May cause cancer.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Carc. 1B: Carcinogenicity, Hazard Category 1B

(Contd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 16.06.2015 Revision: 16.06.2015

Trade name: Casite Motor Honey Engine Oil Leak Stopper

(Contd. of page 10)

· Sources

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com